



TECHNICAL CHARACTERISTICS

senso Lock

			Lock 30	Lock 20
Total thickness	EN 428	mm	4.0	3.4
Thickness of the wear layer	EN 429	mm	0.30	0.20
Weight: Mass per unit area	EN 430	g/sqm	7760	6782
Dimensions	EN 427	cm	planks: 94 x 15 tiles: 30.3 x 60.7	planks: 93.5 x 14.9 tiles: 30.7 x 60
Surface treatment	-	-	PUR+	PUR
Packaging	-	planks / tiles	14 planks 10 tiles	14 planks 10 tiles
Surface / packaging	-	sqm	planks: 1.97 tiles: 1.84	planks: 1.95 tiles: 1.84
Norm / Product specification	-	-	EN 649	
European classification	EN 685	class	23/31	22
VOC rating (French norm)	-	-	A+	
Fire rating - Classification	EN 13501-1	class	B _{fl} -s1	
Wear Group	EN 649	group	T	
Impact sound insulation	EN ISO 717/2	dB	4	-
Room impact noise	NF S 31074	class	C	-
Slip resistance wet: ramp test with oil	DIN 51 130	class	R9	
Dimensional stability after exposure to heat	EN 434	%	≤ 0.15	
Residual indentation	EN 433	mm	≤ 0.10	
Thermal conductivity	EN 12 524	W/(m.k)	0.25	
Colour fastness	EN 20 105 - B02	degree	≥ 6	
Guarantee residential use	-	year	12	11
TVOC after 28 days	-	µg/m ³	< 100	
Edges			V Style	Straight edges

CE MARKING



EN 14041



Areas of use: domestic use



HEALTH

- Formaldehyde-free
- Lead-free, no heavy metals
- Solvent-free
- No harmful plasticizer
- Low VOC emission
- No glue

ENVIRONMENT

- 100% recyclable
- ISO 14001
- Soapy water cleaning

