



# senso Lock Plus

## TECHNICAL CHARACTERISTICS

Total thickness	EN 428	mm	5.0
Thickness of the wear layer	EN 429	mm	0.55
Weight: Mass per unit area	EN 430	g/sqm	8260
Dimensions	EN 427	cm	105 x 18 29.3 x 63.8
Planks / Tiles per box			10 planks = 1.89 sqm 8 tiles = 1.50 sqm
Norm / Product specification	-	-	EN 649
European classification	EN 685	class	33/42
Fire rating - Classification	EN 13501-1	class	B <sub>f1</sub> -s1
Static electrical peopersity	EN 1815	kV	< 2
Slip resistance wet: ramp test with oil	DIN 51 130	class	R9
Wear Group	EN 649	group	T
Dimensional stability	EN 434	%	≤ 0.15
Residual indentation	EN 433	mm	0.05
Sound insulation	EN ISO 717/2	dB	5
Room impact noise	NF S 31074	class	C
Thermal conductivity	EN 12 524	W/(m.k)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Surface treatment	-	-	PUR+
Floor heating	-	-	OK - T° < 28°C
Guarantee residential use	-	year	15
TVOC after 28 days	ISO 16000-6	µg/m <sup>3</sup>	< 100


### CE MARKING



EN 14041



Areas of use: domestic use



#### HEALTH

- Formaldehyde-free
- Lead-free, no heavy metals
- Solvent-free
- No harmful plasticizer
- Low VOC emission
- No glue

#### ENVIRONMENT

- 100% recyclable
- ISO 14001
- Soapy water cleaning

